

Office of River Protection

High Level Waste Corporate Board March 31, 2008

Delmar Noyes Acting Assistant Manager Tank Farm Project

U.S. Department of Energy




Project Scope

- Storing, retrieving, treating and disposing of tank waste and closing the Tank Farms
- Maintaining Tank Farm infrastructure consisting of 177 underground storage tanks that contain ~53 million gallons of radioactive waste from past processing operations
- Constructing and Operating the Waste Treatment Plant (WTP)
- Decontaminating and Decommissioning the WTP

RPP Mission Life-Cycle






Hanford Tank Waste Cleanup Challenge



Hanford Site:

- 177 underground storage tanks
 - •149 Single-Shell Tanks
 - 28 Double-Shell Tanks
- ~194 million curies of radioactivity in tanks
- ~190,000 tons of chemicals



Hanford Tank Farms







Hanford Tank Farm Overview


- 53-million-gallons-of-tank-waste
- 177 underground tanks
 - 149 Single-Shell Tanks (SSTs)
 - -28 Double-Shell Tanks (DSTs)
- 7 SSTs Retrieved to date

200 East Area


- -SSTs = 11 M gal
- -DSTs = 21 M gal

200 West Area

- SSTs = 19 M gal
- DSTs = 2 M gal



Hanford 200 Area Plateau



Mission – Our focus remains the same

- Cleanup and closure of Tank Farms
 - safe operations
 - maximizing tank retrievals
 - develop and deploy retrieval technologies (10 to date) without compromising double-shell tank space needed for efficient treatment operations
- Construction of the Waste Treatment Plant by 2019; and Low-Activity Waste Vitrification Facility by 2012
- Ensuring adequate infrastructure is in place to feed WTP when it comes online
- Evaluating a viable waste treatment configuration to begin making glass as soon as possible with early LAW or supplemental treatment technologies

Tank Farm Project Status


Transferred over 294,000 gallons of radioactive and hazardous waste from single-shell tanks to safer double-shell tanks

- Seven tanks have been emptied to date
- Processed more than 2 million gallons of waste
 - reducing the waste volume in the double-shell tanks by more than 1.2 million gallons

March 12, 2008



Richland Operations Office Cesium and Strontium Capsules



- RL is storing the 601 strontium and 1,335 cesium capsules at the Waste Encapsulation and Storage Facility (WESF)
- · Capsules are considered HLW
- Baseline planning is to ship directly to the high-level waste repository in DOE Standard Canisters without further processing.
- RL strategy is to seek regulatory relief from RCRA waste designation as preliminary performance assessment modeling indicate that the regulated materials do not present a risk to human health and environment.


Cesium and Strontium Capsules

- Cesium and strontium double encapsulated 1974 – 1985
- Capsules are 6.6 cm dia x 52.1 cm long (2.6 in. dia x 20.5 in. long)
- 1335 Cesium capsules contain:
 - Cesium chloride
 - —¹³⁷ Cesium ¹³⁷m Barium 362 x 10¹⁶ Bq (99 Mci)
- 601 Strontium capsules contain
 - Strontium fluoride
 - ⁹⁰Strontium ⁹⁰Yttrium 157 x10¹⁶ Bq (44 Mci)






River Protection Project



Hanford Defense Production Facilities (1944 - 1990)




March 12, 2008


ORP-08-0011

Hanford Tank Waste Would Cover


a Football Field 150 Feet Deep



Hanford High-level Waste Radioactive Underground Storage Tanks are Large



Single-Shell Tanks




- 149 Tanks Constructed 1943-64
 - ~210 m³ to 3,800 m³ Capacity (55 kgal to 1 Mgal)
 - Bottom of Tanks at Least 50 m (150 Feet) Above Groundwater
 - No Waste Added to Tanks Since 1980
- Tanks Currently Contain:
 - ~121,000 m³ (32 Mgal) of Salt Cake, Sludge, and Liquid
 - ~370 x 10¹⁶ Bq (100 MCi)
- 67 Are Assumed to Have Leaked
 3,800 m³ (~1 Mgal)

29110022.1 Rev. Date 7/23/02




Cross-Sectional Views of Hanford Single-Shell Tanks




29003050.61

Double-Shell Tanks



- 28 Tanks Constructed Between 1968-86
- ~3,800 m³ to 4,300 m³ (1 to 1.14 Mgal) Capacity
- Tanks Currently Contain
 - ~ 83,000 m³ (22 Mgal) of Mostly Liquids (Also Sludges and Salts)
 - ~ 333 x 10¹⁶ Bq (90 MCi)
- None Have Leaked


29110022.2 Rev. Date 7/23/02




March 12, 2008

ORP-08-0011

Double-Shell Tanks under construction









March 12, 2008







March 12, 2008



March 12, 2008



Program History

- 1956: First tank leak discovered
- 1958: First waste treatment plan, calcine 1/3, solidify 2/3 in tanks -- not implemented
- 1960s-1970s: Concern over more tank leaks and lack of tank space, growing interest in radioisotopes
 - Removed primary heat producers (Sr-90 and Cs-137)
 - Operated in-tank solidification systems
 - Encapsulated Sr-90 and Cs-137
 - Constructed double-shell tanks
- 1975: First waste management EIS issued

Program History (cont.)

- 1980: Stopped adding waste to single-shell tanks
- 1983: DOE issues plan. Savannah River HLW first, Hanford second, Idaho third. For Hanford:
 - Retrieve DST waste, divide in two fractions, vitrify HLW for repository disposal, grout LAW and dispose onsite
 - Solidify SST waste and dispose in place
 - EIS preparation started
- 1986: Last eight double-shell tanks constructed

Program History (cont.)

- 1987/1988: EIS/ROD issued. Followed plan except for:
 - Disposal of SST waste in place not acceptable to public
 - SST decision deferred until additional development and evaluation
- 1989: Grout facility immobilized 1 million gallons of waste, Hanford Waste Vitrification Plant designed
- 1989: Tri-Party Agreement signed
- 1990: Tank safety issues identified, 54 tanks placed on "watch list"

March 12, 2008

Program History (cont.)

- 1991: Secretary Watkins directed formation of the Tank Waste Remediation System as a single project
- 1993: Hanford Waste Vitrification Project terminated because:
 - Tank waste safety issues would take active intervention
 - Modification of existing facility for waste treatment could not achieve full environmental compliance
 - Policy decision to retrieve all tank waste, increased volume of waste to be treated four-fold
- 1994: New strategy developed and Tri-Party Agreement amended

- 1995: Decision to privatize waste treatment
- 1996-97: EIS/ROD issued
 - All waste retrieved and vitrified
 - Project to be done in two phases
 - Decision on capsules deferred
- 1997: Cross-site transfer line constructed
- 1998: Office of River Protection formed
- 1999: Retrieved waste from single-shell tank C-106

• 2000: Privatization terminated and contract awarded

to Bechtel National Inc.


- 2001: Last tanks removed from the Watch List
- 2002:
 - 133 Single-shell tanks interim stabilized
 - Waste retrieval Cold Test Facility constructed
 - Waste Treatment Plant construction started




CH2MHILL Hanford Tank Cleanup Status Medicular Probability




Retrieval Summary Updated through July 1, 2007







Acid Dissolution




Modified Sluicing




Vacuum Retrieval



Saltcake Dissolution




Water Lance (Salt Mantis)



Mobile Retrieval Tool (Sand Mantis)






Mobile Retrieval Tool (FoldTrack)



Mobile Retrieval System - Future



Tank Space

- Waste will remain in most SSTs longer consistent with extended treatment mission duration
- SST Integrity Program to provide improved information
- DST space to retrieve SST wastes limited until WTP startup

Retrievals

- Limited to ~ one SST retrieval per year until WTP startup
- Early LAW potentially enables 5 10 additional SST retrievals before full WTP startup
- Improved technologies desirable;
 - hard heel removal
 - known and suspected leaker tanks

Tank Closure


- No closures envisioned prior to TC&WM EIS ROD
- TPA Appendix I identifies RCRA closure process
- DOE must determine tank residuals are not HLW prior to closure

How is the Vitrified Waste Stored?

- High Level Waste Canisters
 - 2' x 14.5'
 - 6,600 pounds of glass
 - Temporarily stored in Hanford's Canister Storage Building until national repository built
 - Plan to generate 12,000 15,000 canisters
- Low Activity Waste Containers
 - $-4' \times 7.5'$
 - 13,000 pounds of glass
 - Stored at Hanford's Central Plateau
 - Plan to generate 30,000 40,000
 Containers




Better, Faster, Cheaper



March 12, 2008

ORP-08-0011

- Multiple waste forms create multiple sampling challenges
 - Supernatant liquid
 - Interstitial liquid
 - Sludge
 - Saltcake
 - Slurry



Evolution of Sampling Technologies


Chemical Sampling

- Grab Sampling
- Finger Trap
- Core Sampling

Residual Waste Sampling

- Off-Riser Sampling
- Alligator






Alligator

Sampling Outside the Tanks

- Direct Push
- Boreholes

Continued Waste Management


- Ultrasonic testing of doubleshell tanks
- Cold Test Facility



Where do we go From Here?

- New technologies will be vital to maintain retrieval progress
- Complete retrieval of C-109
- Initiate retrievals in C-104 and C-110
- Major upgrades to 242-A Evaporator
- Organizational realignment to meet the challenges of the future
 - Waste retrieval
 - Waste management
 - Infrastructure maintenance


The Plan: Send ~97% of Radioactivity and ~5% of Waste Volume to Yucca Mountain



Extensive Tank Characterization Completed

- Over 600 tank samples taken since 1994
- Hanford Historical Process Model allows projection of sample data to all tank contents
- Extensive library of tank data
- Over 1M analytical records
- Over 40M cells of data; 634 chemical constituents and physical properties included
 - Best Basis Inventory estimates for all tanks (sampled and projected)
 - Analytical results from tank samples
 - Tank vapor sample data, temperatures and waste levels
 - Ongoing sampling to support operation We know what's in the tanks

TANK TREATMENT & DISPOSAL PATHWAYS



Primarily Studge – HLW Feed
Primarily Studge – HLW Feed
RH -TRU
Contact Handled – TRU Tanks

O Low Curie Feed - Supplemental Treatment
O Retrieval Complete

Background

- Tank waste to be disposed through several pathways
 - WTP-HLW


- Supplemental treatment

- WTP-LAW

- TRU
- Two types of WTP waste feed
 - LAW (Soluble saltcake and supernatant)
 - HLW (Insoluble sludges and cesium removed from supernatants)
- Retrievals planned based on keeping LAW and HLW process rates balanced
 - Evaluated using Hanford Tank Waste Operations Simulator (HTWOS) model
- Feed conditions and constraints described in Interface Control Documents (ICD-19)

March 12, 2008

ORP-08-0011



Simulates Waste Treatment Mission

- Mix Streams
- Partition Streams (Evaporator, IX, S/L Separation, Wash & Leach)
- Rule Based
- Dynamic (time-varying flows and compositions, discrete events)

Subject to Constraints

- Tank Space
- Production Rates
- Transfer Rates
- Equipment Availability
- Simultaneous Transfers
- Other Relevant Constraints

Not Addressed

- Reaction Kinetics
- Thermodynamics
- Heat Transfer
- WTP Details (internal stream compositions, cycle time, non-waste sodium additions, tank sizing and utilization, actual pretreatment throughput impact on melter)

Background

- Tank waste to be disposed through several pathways
 - WTP-HLW


- Supplemental treatment

- WTP-LAW


- TRU
- Two types of WTP waste feed
 - LAW (Soluble saltcake and supernatant)
 - HLW (Insoluble sludges and cesium removed from supernatants)
- Retrievals planned based on keeping LAW and HLW process rates balanced
 - Evaluated using Hanford Tank Waste Operations Simulator (HTWOS) model
- Feed conditions and constraints described in Interface Control Documents (ICD-19)

March 12 2008


Cumulative Waste Retrieved



Injury Cases vs. Volume Retrieved




Retrieval Cost By Tank



March 12, 2008

ORP-08-0011



3 M gal candidate TRU → Package for WIPP Disposal

Eliminates 1500 HLW Canisters

~1% curies and 5% volume

Tank Farm Facility Definitions

• Supplemental Pre-treatment

- Major facility within the tank farms to remove the high level fraction of waste.
 Supplemental Pretreatment supports:
 - » Supplemental LAW facility in the 200 West (e.g. Bulk Vitrification)
 - » and/or supports LAW First

Demonstration Bulk Vitrification System (DBVS)


- Purpose is to demonstrate the viability of this down-selected technology as a supplemental LAW facility
- Research and Development facility that will produce up to 50 boxes of glass using Tank
 S-109 waste


Bulk Vitrification

- Production scale DBVS: One option for LAW Supplemental Treatment. Major facility within the Tank Farms to supplement the Waste Treatment Plant LAW capacity
- Processes up to 50% of the Low Activity Waste
- Baseline has a 4-line plant in the 200 West and 4-Line Plant in the 200 East Area

Tank Treatment & Disposal Pathways

200 West





- O Primarily Saltcake or Supernatant- ILAW Feed
- Primarily Sludge HLW Feed
- Remote Handled -TRU
- Contact Handled TRU Tanks
- O Candidate Low Curie Feed Supplemental Treatment
- O Retrieval In Progress

- Candidate Sludge for Supplemental HLW Pretreatment (Note: A and SX Farm tanks have Moderate Access for sludge retrieval)
 - Candidate Medium Curie Feed to Supplemental LAW Pretreatment (Primarily Saltcake or Supernate)
- Retrieval Completed

Tank Waste Retrieval

- Retrieval of waste from older single-shell tanks continues
- Technologies based on waste characteristics and tank physical condition
- Demonstrating achievability of 99% waste retrieval
- Working with State of Washington and Nuclear Regulatory Commission on retrieval effectiveness
- Managing available Double-Shell tank space







March 12, 2008

Integrated Disposal Facility

